

Linear Imager Barcode Scanner

The SocketScan S700 1D linear barcode scanner with Bluetooth wireless technology scans on paper or screen. It has a lightweight, ergonomic structure, and a long-lasting battery to withstand entire work days. The lights for battery, Bluetooth and scanning notifications make the scanner more intuitive to use. The S700 is designed to be software compatible with all applications. Updates on operating systems may alter the devices' performance.

This scanner is ideal for retail POS, field service, inventory management, asset tracking and more. Use our Companion App for easy set up and configuration.

For the most reliable and consistent performance, please verify with your application provider that Socket Mobile's latest Capture SDK was implemented in your app.



Certified by Apple[®] for iOS devices (iPad[®], iPhone[®], iPod Touch[®] devices) and compatible with Android and Windows[®]

Features

- •Bluetooth Wireless Technology Connects easily to a wide range of Bluetooth enabled smartphones, tablets, notebook and desktop computers
- Certified by Apple[®] for iOS devices Guaranteed Compatibility With Capture SDK integrated in over 700+ applications, Socket Mobile scanners are one of the most natively integrated scanners available today. Socket Mobile Scanners are also 100% compatible with any application out-of-the-box in HID (keyboard emulation) mode.
- Compatible with all Android and Windows devices and applications
- •Scanning Reads all common 1D / linear and stacked barcodes
- Exceptional Ergonomics Small, lightweight, and fits perfectly in the hand for comfortable use over extended periods
- Long-Lasting, Replaceable Battery Power to last a full work day, up to 9 hours of consistent usage
- •User Indicators Intuitive LEDs, beeps, and vibrations let users know battery, Bluetooth connection and scanning status
- User Feedback Audible tones and hand pulsation
- **Color Options -** Black, blue, green, red, white and yellow colors enable style, corporate-branding for personalization and the bright colors are easier to find in most work environments
- •Application Integration Socket Mobile's Capture SDK enables integration in your applications to improve business productivity with fast, efficient and reliable data transfer over Bluetooth wireless technology
- •Wearable Includes wrist strap. Holster, lanyard and retractable clip available (sold separately)
- Designed and Assembled in the USA
- Developer Support Available
- •1-Year Warranty



Single Package includes


(1) SocketScan S700, 1D Barcode Scanner (1) Charging Cable

The S700 is available in 6 colors:

্রন্দ্রনি ভ

- (1) Wrist Strap
- (1) Get Started Insert





Socket Mobile Companion Download for easy setup of scanner

S700 w/ S700 w/ Colors: **S700** White Charging **Black Charging Dock** Dock Black: CX3803-2563 CX3805-2565 Blue: CX3360-1682 CX3465-1933 CX3484-1979 Green: CX3395-1853 CX3463-1931 CX3524-2126 Red: CX3391-1849 CX3461-1929 CX3522-2124 White: CX3397-1855 CX3464-1932 CX3483-1978 Yellow: CX3523-2125 CX3393-1851 CX3462-1930

Optional Accessories





Scanner:	Standard one year limited warranty			
Accessories:	90 days			
Extended Warranty: (sold separately)	www.socketmobile.com/socketcare			

Technology:	1D Barcode Linear Imager
Aimer:	Visible Red LED (625 nanometers)

Scanning Performance

Symbologies: Limited, CSI-128, Interleaved 2 of 5, Ode 39, Code 39, Code 128, EAN-13/JAN, EAN-8/ JAN, GSI Databar, GSI Databar Expanded, GSI DataBar Limited, GSI-128, Interleaved 2 of 5, Matrix 2 of 5, UPC-4, UPC-EI Scan Angle: 53° Optical Resolution: 5 mil/01 mm Print Contrast: 30% minimum Reading Distance: in./cm in./cm istance: in./cm in./cm istance: in./cm istance: in./cm i	Supported Barcode Symbologies:Bookland EAN, Chinese 2 of 5, Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13/JAN, EAN-8/ JAN, GS1 Databar, GS1 Databar Expanded, GS1 DataBar Limited, GS1-128, Interleaved 2 of 5, Matrix 2 of 5, UPC-A, UPC-E1Scan Angle:53°Optical Resolution:5 mil/0.1 mmPrint Contrast:30% minimumReading Distance:in./cm		Code 39, Code 128, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 DataBar					
Symbologies: JAN, GSI Databar, GSI Databar, Expanded, GSI DataBar Limited, GSI-128, Interleaved 2 of 5, Matrix 2 of 5, UPC-A, UPC-E1 Scan Angle: 53° Optical Resolution: 5 mil/01 mm Print Contrast: 30% minimum Reading Distance: in./cm S700	Symbologies:JAN, GS1 Databar, GS1 Databar Expanded, GS1 DataBar Limited, GS1-128, Interleaved 2 of 5, Matrix 2 of 5, UPC-A, UPC-E1Scan Angle:53°Optical Resolution:5 mil/0.1 mmPrint Contrast:30% minimumReading Distance:in./cm		Limited, GS1-128, Interleaved 2 of 5, UPC-A, UPC-E1					
Optical Resolution: 5 mil/0.1 mm Print Contrast: 30% minimum Reading Distance: in./cm Image: State of the state o	Optical Resolution: 5 mil/0.1 mm Print Contrast: 30% minimum Reading Distance: in./cm	Symbologies: J	JAN, GS1 Databar, GS1 Databar Expanded, GS1 DataBar Limited, GS1-128, Interleaved 2 of 5, Matrix					
Print Contrast: 30% minimum Reading Distance: In./cm 4.0 in. / 10.0 cm 2.0 in. / 5.0 cm d t h h f 2.0 in. / 5.0 cm d t h h h f 2.0 in. / 5.0 cm d t h h h f f 2.0 in. / 5.0 cm d t h h h f f f f f f f f f f f f f f f f	Print Contrast: 30% minimum Reading Distance: in./cm	Scan Angle: 5	53°					
Reading Distance: in./cm 4.0 in. / 10.0 cm 4.0 in. / 10.0 cm 2.0 in. / 5.0 cm id in./cm id in./cm id in./cm in./cm in./cm id in./cm	Reading Distance: in./cm	Optical Resolution:	5 mil/0.1 mm					
Distance: in./cm 4.0 in./ 10.0 cm 4.0 in./ 10.0 cm 4.0 in./ 5.0 cm 4.0 in./ 5.0 cm 4.0 in./ 5.0 cm 4.0 in./ 5.0 cm 4.0 in./ 10.0 cm	Distance: in./cm	Print Contrast:	30% minimum					
In. 0 5 10 15 20 25 cm 0 12.7 25.4 38.1 50.8 63.5	S700 S700	Reading	in./cm 4.0 in. / 10.0 cm 4.0 in. / 10.0 cm 2.0 in. / 5.0 cm 4.0 in. / 10.0 cm 5700 5700 5700 5700 5700 5.0 cm 4.0 in. / 10.0 cm 5.0 c					

1D codes 3.5 to 41 cm (1.4 to 16.1 in) Resolution Depends on barcode size, symbology, label media.

Resolution	Near	Far	
5 Mil	2.8 in./ 7 cm	5.9 in./ 15 cm	
10 Mil	1.4 in./ 3.5 cm	11.0 in./ 28 cm	
15 Mil	1.8 in./ 4.5 cm	16.1 in./ 41 cm	
13 Mil	1.6 in./ 4.0 cm	12.6 in./ 32 cm	

Battery:	2 AA NiMH rechargeable batteries (replaceable battery)
Charge Time:	~6 Hours
Battery Life:	500 charge-discharge cycles
Battery Life Per Full Charge:	Standby time: over 20 hours Active Scan Time: 80,000 scans within 9 hours (based on 2 scans every 1 second) 7,000 scans within 7 hours (based on 1 scan every 4 seconds)
Note:	Battery life varies depending on ambient temperature, ambient light and age of battery. For more battery information <u>click here</u> .
Number of Batteries Used:	2
Weight of battery:	54.5g
Percentage Lithium:	N/A
Battery mAh:	2000 mAh
Number of cells per battery:	1
Watt Hours per battery:	2.4
Type of Cell (ex. AA):	AA
Chemical Composition (ex. Alkaline):	Nickel Metal Hydride
Lithium Content:	N/A
Battery Voltage:	2.4v
Hazmat UN Number:	N/A
ROHS Compliance Indicator:	Yes, Included with Scanner
Country of Origin:	China
Commodity Code:	8507.50.0000

Bluetooth (wireless connection)

Bluetooth Radio:	Class 2 Bluetooth, version 2.1 + EDR (Enhanced Data Rates) with 56-bit data encryption
Bluetooth Range:	Up to 10 m (33 ft.) depending on environment, range limit is usually due to the Host Device (phone, tablet or notebook)
Bluetooth Profiles:	Basic Mode - Human Interface Device (HID)*, Application Mode - Serial Port Profile (SPP) and Application Mode - MFi-SPP. Some Operating Systems or smartphone/tablet models may support only one profile. * <i>By default, the scanner is set to Basic Mode (HID).</i>

User Environment

Ambient Light:	From 0 to 100 000 lux From pitch black to direct sun light
Operating Temperature:	0° to 45° C (32° to 113° F)
Storage Temperature:	-40° to 70° C (-40° to 158° F)
Relative Humidity:	95% at 60° C (140° F) (non-condensing)
Drop Specifications:	4 ft. to linoleum

Operating System compatibility

Android OS: Basic Mode (HID)* & Application Mode (SPP)

Apple iOS: Basic Mode (HID)* & Application Mode (MFi-SPP)

Mac OS: Basic Mode (HID)* only

Windows OS: 10, 8, and 7: Basic Mode (HID)* & Application Mode (SPP)

Compatible with devices supporting Basic Mode (HID)* protocol

Language Support: ANSI, English UK, English, French, German, Italian, Japanese, Polish, Spanish and Swedish *By default, the factory settings of the Socket Mobile Scanners are set to Basic Mode (keyboard emulation: HID). In order to use the scanner with an application using Capture SDK, the scanner must be configured in Application Mode (Bluetooth Serial Port Profile: SPP).

Certified by Apple[®] for iOS devices (iPad[®], iPhone[®], iPod Touch[®]) and compatible with Android and Windows[®].













Common Uses

Warehouse management		
Shipping and Receiving		
Field Sales/Service		
Hospitality		

Certification & Regulatory

Bluetooth SIG	etooth SIG: Declaration ID: D030473 QD ID: 82009						
Electrical Safe	ty:	Certified to IE	C 60950-1, UL 6095	0-1, CAN/C	SA C22.2		
Environmenta	l:	Environmenta	l: RoHS EN 50581				
EMI / RFI:		FCC Part 15 Cla FCC ID: T9J-RN IC ID: 6514-RN Telec: R 201-12	42	003, C-Tick	, CISPR 22, CE E	N55022, EN55024	, TELEC
LED Safety:		IEC/EN 62471 (EXEMPT GROUP)				
ISO 9001 Accre	editation	A C C R E D I T E ISO/IEC 17021 MANGEMENT SYSTEMS CERTIFICATION BODY	ISO 9001				
F©	Œ		ndustry Canada		SRRC	X WEEE	RoHS
socketmobile.com			sales@socketmobile.com			sales-ianan@s	ocketmobile.com
Worldwide:	+1 510 933 3000		Asia Pacific:	+1 510 933 3122		Japan:	+8190 9808 0518
North America:	+1 800 552 3300		Germany:	+41 62 834 07 8	0	Japan (Toll Free	
EMEA & Russia:	+41 62 834 07 80		Switzerland:	+41 62 834 07 8		Latin America:	+1-510-933-3153
France:	+33 (801) 840504		Switzerland (Toll Free):	+41 (800) 8980	03	Taiwan (Toll Fre	ee) +886 00801491497
Malaysia (Toll Free)	+60 (1800) 818234		UK/Ireland/South Africa:	+44 (800) 0487	363		
©2021 Socket Mobile, Inc. All rights reserved.Socket [®] , the Socket Mobile logo, SocketScan [®] , DuraScan [®] , Battery Friendly [®] are registered trademarks or trademarks of Socket Mobile, Inc. Microsoft [®] is a							

registered trademarks of Apple, Inc., registered in the U.S. and other countries. The Bluetooth[®] Technology word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Socket Mobile, Inc. is under license. Other trademarks and trade names are those of their respective owners.