



1D









CCD



Dual

Interface

IP54

2 Years

**FM100** Stationary Scanners

## **Features**

# Ease of integration.

Compact and easy to integrate design. The small form factor enables easy integration into various solutions. This 1D fixed barcode scanner has an IP54 rating making it dust & water resistant.

# Advance Technology.

Includes core-technology, which is independently designed and manufactured by Newland Auto-ID. Technology includes the optical, CMOS, digitizer, decoder, image processing & embedded systems. The scanner supports all global standard 1D

barcode symbologies. Its reading performance reaches and exceeds global standards. By using the accessories provided, the user can easily set up the scanner to their customer's environment.

# Application scenarios.

Designed for OEM applications, this high performance fixed CCD scan engine can easily be integrated into various solutions such as kiosks, ticketing machines, (Reverse) Vending Machines and many more.

# Suggested industries











**Postal** 

# FM100 Technical specifications

#### **Performance**

CCD 2500 Image Sensor

Red LED (622 nm - 628 nm) Illumination

±60°

ABS

Minimal Print Contrast

Scan Angle Roll ±30°

Scan Angle Pitch ±65°

Field of View Horizontal 40°

Scan Modes Interval Mode, Sensor Mode, Continuous Mode, Delayed Sensor Mode, Command Triggered Mode

Scan Rate 300 scans per second

#### **Data Capture**

Scan Angle Skew

1D All major 1D symbologies, including Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved

2 of 5, ISBN/ISSN, Code 93,UCC/EAN-128, GS1Databar.

### **Physical**

Dimensions (mm) 49.0 \*37.0 \* 26.0 mm

Weight 70g

Material

Interfaces RS-232, USB

**Notifications** Beep, LED indicator

Input Voltage 5VDC ± 5%

Current @ 5VDC Operating 170mA

Current @ 5VDC Standby 65mA

Power Supply Input DC5V, 1.5A

Power Supply Output AC100~240V, 50~60Hz

### **Environmental**

0 ~ 100,000 LUX Ambient Light

**Operating Temperature** -5°C to 45°C

Storage Temperature -40°C to 60°C

Humidity 5%~95% (non-condensing)

IP Rating IP54

## **Accessories**

Standard **USB** Cable

Optional RS232 Cable, Adapter

## Certifications

Hardware FCC Part15 Class B, CE EMC Class B,KC

# Warranty

Standard 2 years

**Newland EMEA HQ** 

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2021, all rights reserved

