

T-25

METAPACE T-25

Affordable top-quality
POS printer

Technical Specifications

PRINT

Printing method	Direct thermal
Print speed	max. 250mm/sec
Consumables	Thermal paper
Paper	Width: 58/80mm/s, max. ø: 102mm
Print width	45/72mm
Paper supply	Easy-load
Resolution	8 dots/mm (203 dpi)
Character size	Font A: 12 x 24 / font B: 9 x 24
Barcodes	All standard 1D barcodes & PDF 417

ELECTRONICS

Emulation	ESC/POS
Sensor	Paper near end, paper end, cover open
Memory	512KB ROM
Power supply	External, 100–240V AC, 24V DC
Reliability	100 km TPH, 1,000,000 cuts, 60,000,000 lines

INTERFACES

I/F Ports	USB, RS232, 1x drawer kickout (RJ12)
-----------	--------------------------------------

SOFTWARE

Operating system	Windows XP, Windows 10, Vista (32 / 64-bit), 7 (32 / 64-bit), 8 (32 / 64-bit)
------------------	--

HOUSING

Dimensions (WxDxH)	142 x 212 x 149mm
Colour	Black

WARRANTY

Period	2 years
--------	---------

SPECIFICS

Package contents	USB cable (A/B), PSU + power cord (EU), CD (drivers, utilities), QSG, test receipt roll
------------------	--

Highlights

- + Robust receipt printer for retail and hospitality
- + Paper buffer for 10 cm receipt rolls
- + Maximum print speed: 250mm/sec.
- + Integrated auto cutter for up to 1 million cuts
- + Complete package with drivers, cables, power supply and much more

