



1D



2D



DPM



IP64



USB



NVF260

Stationary Scanners

Features

DPM Decoding.

With a new generation of industrial decoding, the NVF260 is excellent at reading DPM barcodes even on curved surfaces.

Advanced Illumination.

The NVF260's blue illumination ring helps to reduce bottlenecks in the scanning process by avoiding the reflection from materials with metal surfaces.

Impressive Image Sensor.

With a 1280x800 megapixel imager, the NVF260 can decode up to 3-millimetre barcodes.

Industrial Design.

Built with an IP64 housing, the NVF260 easily resists water and dust. The medical-grade housing is also able to be sterilized without alcohol damage.

Suggested industries



Healthcare



Industrial



Manufacturing

NVF260 Technical specifications

Performance

Image Sensor	1280x800 CMOS
Illumination	Diffuse: ring of blue LED
Depth of Field Data Matrix (10mil)	0-25mm
Depth of Field QR (15mil)	0-30mm
Minimal Print Contrast	50%
Scan Angle Roll	360°
Scan Angle Pitch	±40°
Scan Angle Skew	±40°
Field of View Horizontal	32.7°
Field of View Vertical	20.7°

Data Capture

1D	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Code 128, Code 39, Codabar, UCC/EAN 128, AIM128, Interleaved 2 of 5, ITF-14, ITF-6, Standard 2 of 5, Matrix 2 of 5, COOP 25, Industrial 2 of 5, Plessey, MSI Plessey, Code 11, Code 93, ISBT128, Deutsche 14, Deutsche12
2D	QR Code, Data Matrix

Physical

Dimensions (mm)	Height: 100mm, Diameter: 65mm
Weight	347g
Interfaces	USB TYPE-C
Notifications	Beep, LED indicator
Input Voltage	5VDC±5%
Current @ 5VDC Operating	230mA (typical), 330mA (max)
Power Consumption	1150mW (typical)

Environmental

Operating Temperature	0°C to 50°C (32°F to 122°F)
Storage Temperature	20°C to 70°C (-4°F to 158°F)
Humidity	5% to 95% (non-condensing)
Electro Static Discharge (ESD)	±8 KV (direct discharge); ±15 KV (air discharge)
Drop	1.2m
IP Rating	IP64

Certifications

Hardware	FCC Part15 Class B, CE EMC Class B
----------	------------------------------------

Newland EMEA HQ

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2022, all rights reserved

